



## Full HD Telepresence, Tailored to your Environment

### Superior telepresence is now achievable beyond the board room.

Now more users in more places can realize the benefits of telepresence to improve their productivity, working face-to-face with colleagues in remote locations.

LifeSize Conference 200 is the next step in telepresence - Full HD video, 1/3 the bandwidth of comparable solutions and designed for deployment beyond the fixed telepresence suite.

With the LifeSize Conference 200 solution, you get the most advanced technology and most immersive experience available today: Full HD, 1080p30, 720p60, and 720p30 dual streams to share data and documents in full motion, high definition. You also get an embedded multipoint control unit (MCU), complete with transcoding.

### Flexibility is made simpler than ever.

Our exemplary attention to the human experience ensures that the LifeSize Conference 200 system is easy to use. And with built-in AMX panel software, calling is made simple with one-button dialing. Committed to open architecture, our proven interoperability provides complete integration into your existing communications infrastructure.

LifeSize Conference 200 means the end of costly, proprietary telepresence solutions that are too expensive and too awkward to deploy throughout your organization.

### Human clarity becomes...remarkable.

Beyond technologies, over and above service and support, LifeSize Conference 200 enables facial expressions, body language and gestures to transcend geography. Your work teams, wherever they are, get incredible, lifelike clarity.

Review the LifeSize Conference 200's capabilities. You'll discover remarkable video communications that transports user experiences across cities, countries and continents. The LifeSize difference is the LifeSize experience.

## LifeSize Conference 200 Key Features

**Video Quality** HD Telepresence  
1920x1080 - 30 fps or  
1280x720 - 60 fps  
16x9 format

### HD Monitors



### HD Cameras



### HD Audio



**External Audio, Video & Data Input/Output**

Audio: 4 in, 2 out  
Video: 9 in, 4 out  
Data: 1 in, 1 out

### Point-to-Point HD Telepresence



**Conference Room Telepresence Configuration**



# Product Specifications - LifeSize® Conference 200™

## System Components

3 x LifeSize Room 200 Codecs  
4 x LifeSize Cameras 200\*  
1 x LifeSize Phone  
1 x LifeSize Conference software\*\*  
Power supplies  
Cables

\* 1 LifeSize Camera 200 used as full PTZ camera for videoconference mode

\*\* Software applicable to AMX control panel

## System Modes

Telepresence  
- Multi-codec HD telepresence solution  
Videoconference  
- Dual monitor HD videoconferencing solution  
(See LifeSize Room 200 product data sheet)

## Communications

2.5 Mbps – 18 Mbps  
(768Kbps – 6.0Mbps per codec)

## Multiple Displays

Support for three Full High Definition video monitors  
Support for one Full High Definition data monitor  
Any high definition 1080p HDMI/DVI-I monitor (1920x1080) is supported  
LifeSize recommends all three video monitors be identical in manufacturer and size to guarantee quality of the video display  
LifeSize recommends the following size for all monitors:  
All three video monitors should be between 58" and 65"  
The data monitor should be between 42" and 50"

## Full High Definition Camera

Support for three cameras attached to three codecs (primary input)  
Resolution: 1920x1080, 30fps or 1280x720, 60fps  
Camera supports locked position and focus  
3 x 2.9M/10 ft. HDMI cables

## Video Specifications / Video Resolution

1.7 Mbps or higher (1920x1080p30) per codec  
1.1 Mbps or higher (1280x720p60) per codec  
768Kbps (1280 x 720p30) per codec

## Video Standards

H.261, H.263, H.263+, H.264 and H.239

## Video Formats

High Definition, 16x9 aspect ratio

## Video Inputs (9 Inputs)

4 x Full High Definition Cameras  
- One per codec in primary camera inputs  
- One for center codec for videoconference mode  
1 x DVI-I  
1 x LifeSize Camera  
1 x Composite  
1 x S-Video  
1 x Component  
- Center codec only

## Video Outputs (4 Outputs)

3 x HDMI  
- One per codec to primary video monitors  
1 x DVI-I  
- One from center codec to secondary data monitor

## Fully Integrated, High Definition Audio Conference Phone

16 omni-directional microphones in Circular Array with beam forming technology for high quality performance  
100Hz up to 16kHz for wideband support  
Powered directly by center codec through cable

## Audio Standards

G.711, G.722, G.722.1C (Polycom® Siren14™).  
G.728, G.729, MPEG-4 AAC-LC

## Audio Inputs (4 Inputs)

1 x RJ-45 for LifeSize Phone  
2 x 3.5mm line level in  
1 x 3.5mm Mic In  
- All inputs above are attached to center codec only

## Audio Outputs (2 Outputs)

1 x RJ-45 for LifeSize Phone  
1 x stereo line  
- All outputs above for center codec only

## User Interface

Provided through third party control panel with uniquely designed LifeSize Conference software  
Directory/Address book  
Hierarchical address support  
Password protection  
Supported AMX Solution Controller  
- NXT-CV7 7" Modero Widescreen Viewpoint Touch Panel  
- NI-3100 NetLinx Integrated Controller  
- Associated power supply and mounting brackets

## Security

Flash-based web management tool  
Admin and User level passwords  
SNMP security alerts  
Ability to disable HTTP, SSH and TelNet services

## Power

AC Voltage per LifeSize codec  
100-240V, 50-60 Hz, 2.5A

## Environmental Data

Per LifeSize codec:  
Operating Temperature  
0 C (32 F) to 35 C (95 F)  
Operating Humidity:  
15% to 85%, non-condensing  
Storage temperature:  
-20 C (-4 F) to 60 C (140 F)  
Storage humidity:  
10% to 90%, non-condensing

Regulatory Model Number  
LFZ-015

For additional information: [www.lifesize.com/support](http://www.lifesize.com/support)

Information contained in this document is subject to change without notice. LifeSize® is the registered trademark or trademark of LifeSize Communications Inc. All other trademarks are the property of their respective owners. For patents covering LifeSize® products refer to <http://www.lifesize.com/support/legal>. © Copyright 2008. All rights reserved. October 2008.



Corporate Headquarters:  
901 S. Mopac Expressway  
Building 3, Suite 300  
Austin, Texas 78746 USA

Phone: +1 512 347 9300  
Fax: +1 512 347 9301  
Email: [info@lifesize.com](mailto:info@lifesize.com)  
[www.lifesize.com](http://www.lifesize.com)

EMEA:  
LifeSize Communications  
Toll-Free Europe  
008000 999 09 799

APAC:  
LifeSize Communications  
Hong Kong  
Phone: +852 8239 3695